

GENERAL INFORMATION				
Item No.		Gintex-FRC260		
Weight		260 ± 5%gsm		
Composition		100%Cotton		
Full Width		150 ± 2 cm		
Structure		Twill		
Finish		FR Treated		
FR & SPECIAL PERFORMANCE				
Flame Retardant	EN ISO 11611	Class 1 - A1 A2		
	EN ISO 11612	A1 A2 B1 C1 E2 F1		
	NFPA 2112	PASS		
ARC Protective	EN IEC 61482-2	APC 1		
UL Listed	ASTM F1930 (Manikin test)	20.22%		
PHYSICAL PERFORMANCE		warp	weft	
Tensile Strength		ISO 13934-1	1080 N	680 N
Tear Strength		ISO 13937-2	32 N	30 N
Dimensional Stability (After 5 times 60C° washing)		ISO 5077	-1.1%	-1.6%
Abrasion Resistance		ISO 12947-2 12kPA	>10000cycles	
Pilling Resistance		ISO 12945-2 (2000cycle)	4	
COLOUR FASTNESS				
Wash	ISO 105-C06	Change	4-5	
		Stain	4-5	
Rubbing	ISO 105-X12	Dry	4	
		Wet	3	
Light	ISO 105-B02	Level	3-4	
Perspiration	ISO 105-E04	Change	4-5	
		Stain	4-5	

www.gintextiles.com



Xi'an Gintex Co.,Ltd

Jingdu International Building 2#, NO.2999 Changle East Road,
Baqiao District, Xi'an 710038, Shaanxi, China
Tel. +86 29 83350952
info@gintextiles.com