



GINTEX

More Safety More Comfortable

GINTEX-Modsuper250K

MODACRYLIC / ARAMID / NYLON / AS
250 GSM / INTERLOCK



Royal Blue



Red



Navy Blue



Khaki



Sage Green



Orange

Any Color Available

Fabric name	Gintex-Modsuper250K
Fabric weight	250 ± 5% gsm
Composition	Modacrylic / Aramid / Nylon / Anti-static
Full width	160 ± 2cm
Weave	Interlock
Finishes	Normal Finish
Application	Arc Flash Protection
Washing instruction	

FR & SPECIAL PROPERTIES

Flame retardant	EN ISO 11611	Class 1 - A1 A2
	EN ISO 11612	A1 A2 B1 C1 F1
	NFPA 2112	PASS
Arc protection	ASTM F1959	15 cal/cm ²

PHYSICAL PROPERTIES

		warp	weft
Dimensional Stability (After 5 times 60C° washing)	ISO 5077	-1.7	-0.8
Tensile strength, N	ISO 13938-1	976	
PH Value	ISO 3071	7.3	

COLOUR FASTNESS

Wash Fastness	ISO 105-C06	Colour Change	4-5
		Colour Stain	4-5
Rubbing Fastness	ISO 105-X12	Wet	3-4
		Dry	4-5
Light Fastness	ISO 105-B02	Qualification	4-5
Perspiration Fastness	ISO 105-E02	Colour Change	4-5
		Colour Stain	4-5

www.gintextiles.com



Xi'an Gintex Co.,Ltd

Jingdu International Building 2#, NO.2999 Changle East Road,
Baqiao District, Xi'an 710038, Shaanxi, China
Tel/Tax. +86 29 84592644
info@gintextiles.com